


Digital Pressure Gauge Accuracy: $\pm 0.5\%$ FS according to IEC 60770



The digital pressure gauges types DM 80, DM 80-UMS (and DM 80-S) are used for digital indication of measured pressure values, as well as for testing and diagnose purposes in stationary and mobile hydraulic applications.

	Type DM 80	Type DM 80-UMS	Type DM 80-S
Interface:	---	USB	---
Data storage (data transmission as CSV file):	---	8 GB	---
Ambient temperature:	-10...+50°C	-10...+50°C	-10...+50°C
Storage temperature:	-20...+60°C	-20...+60°C	-20...+60°C
Medium ranges -50...+50 and -200...+200 mbar:	-10...+50°C *)	---	---
temperature:	range 0...4 bar absolute:	---	---
	all other pressure ranges:	-40...+125°C	-20...+120°C
Maximal relative humidity:	85% r.h.	85% r.h.	85% r.h.
Material ranges -50...+50 and -200...+200 mbar:	CuZn39Pb3	---	---
pressure port:	range 0...4 bar absolute:	St.st. 1.4404	---
	all other pressure ranges:	St.st. 1.4301	Brass
Material ranges from -50...+50 mbar to 0...4 bar abs.	Ceramic	---	---
membrane:	all other pressure ranges:	St.st. 1.4548	Ceramic
	ranges -50...+50 and -200...+200 mbar:	Epoxy	---
Material range 0...4 bar absolute:	EPDM	---	---
gasket:	all other pressure ranges:	welded **)	H-NBR
Temperature compensated range:	0...50°C	0...50°C	+10...+40°C
Error in temperature ranges -50...+50 and -200...+200 mbar:	$\leq \pm 0.03\%$ FS / °C	---	---
compensated range:	range 0...4 bar absolute:	$\leq 0.005\%$ FS / °C	---
	all other pressure ranges:	$\leq 0.035\%$ FS / °C	$\leq 0.02\%$ FS / °C
Minimum ranges from -50...+50 mbar to 0...4 bar abs.:	10×10^6	---	---
load cycles:	all other pressure ranges:	100×10^6	10×10^6
Power supply:	2 x 1.5 VDC LR6-AA ***)	built-in Li-Ion battery	2 x 1.5 VDC LR6-AA ***)
Max. battery life time:	1500 h	10 h continuously	1500 h
	ranges -50...+50 and -200...+200 mbar:	---	---
Pressure units:	ranges from 0...4 bar abs. to 0...60 bar:	bar, PSI, kPa, MPa, mbar	bar, PSI, kPa, MPa
	ranges from 0...100 bar to 0...600 bar:	bar, PSI, kPa, MPa	bar, PSI, kPa, MPa
	ranges from 0...700 bar to 0...3.000 bar:	bar, PSI, MPa	bar, PSI, MPa
Pressure port:	ranges from -50...+50 mbar to 0...4 bar abs.:	1/4" BSP M acc. EN 837 *)	---
	all other pressure ranges:	1/2" BSP M acc. EN 837	1/4" BSP M acc. EN 837
Indication:	LCD incl. bargraph	LCD incl. bargraph	LCD
PEAK function:	Min. / Max.	Min. / Max.	---
Case material:	Metal (die-cast zinc)	Metal (die-cast zinc)	Plastic
Protection degree:	IP 65	IP 65	IP 40
Weight:	approx. 600 g	approx. 610 g	approx. 390 g
Case with rubber protection cap:	approx. 95-100 mm	approx. 95-100 mm	approx. 95-100 mm
diameter:	without rubber protection cap:	approx. 80 mm	approx. 80 mm

*) For dry gaseous media only! **) no gasket, because of welded diaphragm membrane ***) NOT included in scope of standard delivery

DRUCK & TEMPERATUR Leitenberger GmbH • Bahnhofstr. 33 • 72138 Kirchentellinsfurt • GERMANY

Tel. +49-7121-90920-0 • E-Mail DT-Export@Leitenberger.de • www.druck-temperatur.de

DM 80
DM 80-UMS
DM 80-S

Digital Pressure Gauge $\pm 0.5\%$
DM 80 • DM 80-UMS • DM 80-S

LR-Cal 
DRUCK & TEMPERATUR LEITENBERGER

How to order: Pressure ranges and Order-Codes

Type **DM 80**

Pressure conn.: 1/2" BSP M

Accuracy $\pm 0.5\%$ FS *)

Housing: metal

Protection: IP 65

incl. factory certificate of calibration and black rubber protection cap



Gauge pressure ranges:	Order-Code:
0...10 bar	DM80-0010-0-G12
0...25 bar	DM80-0025-0-G12
0...40 bar	DM80-0040-0-G12
0...60 bar	DM80-0060-0-G12
0...100 bar	DM80-0100-0-G12
0...250 bar	DM80-0250-0-G12
0...400 bar	DM80-0400-0-G12
0...600 bar	DM80-0600-0-G12
0...700 bar	DM80-0700-0-G12
0...1,000 bar	DM80-1000-0-G12
0...2,500 bar	DM80-2500-0-G12
0...3,000 bar	DM80-3000-0-G12

Compound pressure ranges:	Order-Code:
-50...+50 mbar (conn. 1/4" BSP)	DM80-8000-5-G14
-200...+200 mbar (conn. 1/4" BSP)	DM80-8002-0-G14
-1...+16 bar	DM80-9016-0-G12
-1...+25 bar	DM80-9025-0-G12
-1...+40 bar	DM80-9040-0-G12
-1...+60 bar	DM80-9060-0-G12

Absolute pressure ranges:	Order-Code:
0...4 bar absolute (conn. 1/4" BSP)	DM80-0004-ABS-G12

Accessories for DM 80:	Order-Code:
Rubber protective cap with hook for hanging 	DM80-GKS-S-HAKEN
Threaded adapter *)  M1 6x2 female x 1/2" BSP female	DM80-AD-M16-I-G12
Threaded adapter *)  M1 6x2 male x 1/2" BSP female	DM80-AD-M16-A-G12
Small transit case with custom foams 	DM80-KOFFER

*) max.700 bar

*) Accuracy acc. to IEC 60770 (limit point adjustment (non-linearity, hysteresis and repeatability))

Type **DM 80-S**

Pressure conn.: 1/4" BSP M

Accuracy $\pm 0.5\%$ FS (IEC 60770)

Housing: plastic

Protection: IP 40

incl. blue rubber protection cap



Gauge pressure ranges:	Order Code:
0...60 bar	DM80-S-0060-0-G14
Compound pressure ranges:	Order Code:
-1...+3 bar	DM80-S-0003-0-G14
-1...+16 bar	DM80-S-9016-0-G14

Pressure unit BAR or PSI.

Accessories for DM 80-S	Order-Code:
Rubber protective cap with hook for hanging 	DM80-GKS-S-HAKEN
Factory certificate of calibration	DM80-S-WZERT
Threaded adapter  M1 6x2 female x 1/4" BSP female	DM80-AD-M16-I-G14
Threaded adapter  M1 6x2 male x 1/4" BSP female	DM80-AD-M16-A-G14
Small transit case with custom foams 	DM80-KOFFER

Type **DM 80-UMS**

Pressure conn.: 1/2" BSP M

Accuracy $\pm 0.5\%$ FS *)

Housing: metal

Protection: IP 65

Interface: USB-C

incl. factory certificate of calibration and green rubber protection cap



with USB-C interface and **8 GB** data memory
(export as csv file, no special software needed,
the instrument is recognized like an USB
memory stick)



Powered with built-in chargeable Li-Ion battery.

Gauge Pressure Ranges:	Order-Code:
0...25 bar	DM80-UMS-0025-0-G12
0...40 bar	DM80-UMS-0040-0-G12
0...60 bar	DM80-UMS-0060-0-G12
0...100 bar	DM80-UMS-0100-0-G12
0...250 bar	DM80-UMS-0250-0-G12
0...400 bar	DM80-UMS-0400-0-G12
0...600 bar	DM80-UMS-0600-0-G12
0...1000 bar	DM80-UMS-1000-0-G12
0...2500 bar (on request only)	DM80-UMS-2500-0-G12
Compound Pressure Ranges:	Order-Code:
-1...+16 bar	DM80-UMS-9016-0-G12

Accessories for DM 80-UMS:	Order-Code:
Rubber protective cap with hook for hanging 	DM80-GKS-G-HAKEN
Mains charger 110...230 VAC	DM80-UMS-LG
Threaded adapter M1 6x2 female x 1/2" BSP female 	DM80-AD-M16-I-G12
Threaded adapter M1 6x2 male x 1/2" BSP female 	DM80-AD-M16-A-G12
Small transit case with custom foams 	DM80-KOFFER

*) Accuracy acc. to IEC 60770 (limit point adjustment (non-linearity, hysteresis and repeatability))

The type DM 80-UMS is equipped with a 8 GB data memory and has an USB-C connector. The data transfer speed is according to the USB 2.0 standard. The DM 80-UMS is recognized by connected PC/Laptop as an external memory.

The built-in rechargeable lithium-ion battery enables autonomous continuous operation of approx. 10 hours. The charging time of an empty battery is about 3 hours.

The measurement value storage rate can be set: every 10 ms, / 100 ms / 1 sec / 10 sec.
A data record can be also created by pushing the button „REC“.

Due to the extremely large storage capacity, the logging time is approximately as follows:

- with storage interval every 10 milliseconds: approx. 1 year
- with storage interval every 100 milliseconds: approx. 10.1 years
- with storage interval every 1 second: approx. 101.5 years
- with storage interval every 10 seconds: approx. 1015 years

The built-in data memory of the DM 80-UMS will be recognized by the computer as an external memory (like an USB drive). Enables extremely simple reading of the stored data (.csv file) without special software.

Scope of standard delivery of the digital pressure gauge and datalogger DM 80-UMS:

- Device DM 80-UMS with green rubber protection cap
- USB- cable (Micro-USB to USB-A), PC connection to USB-A connector
- Built-in chargeable Li-Ion battery (chargeable with standard 5 VDC output USB chargers)
- Factory certificate of calibration
- Operating manual

Recommended accessories:

- Plug battery charger 110...240 VAC with USB-A connector: order-code [DM80-UMS-LG](#)

DM 80
DM 80-UMS
DM 80-S

Digital Pressure Gauge $\pm 0.5\%$
DM 80 • DM 80-UMS • DM 80-S

LR-Cal **LR**
DRUCK & TEMPERATUR LEITENBERGER

The digital pressure gauges DM 80, DM 80-UMS as well as type DM 80-S are ideal not only for measurement of process pressures (DM 80-UMS with datalogger), but also - in combination with our pressure test pumps - perfect for testing and diagnostic works:



with pressure comparison test pump
LR-Cal LSP 100-H



with pneumatic
pressure test pump
LR-Cal LPP 40



with pneumatic
pressure test pump
LR-Cal LPP 60-T



with hydraulic
pressure test pump
LR-Cal LPP 700/1000



Diagnostic Case **TESTKIT-DM80-UMS-9016**
with pneumatic pressure test pump
LR-Cal LPP 40 and adapters